




Fast Cycling Superconducting Magnets

P.Schnizer on behalf of the magnet group

GSI Darmstadt

p.schnizer@gsi.de

Outline



- The planned facility
- Superconducting magnets for the planned facility
 - fast pulsed synchrotron magnets
 - SIS 100
 - SIS 300
 - Storage rings / SuperFRS
 - other activities
- Conclusions

International Facility for Beams of Ions and Antiprotons

SIS100 (Synchrotron 100 Tm):

- „work horse“
- accelerates heavy ions/protons
- fast extraction to SIS 200 or RIB/Antiproton targets

SIS300 (Synchrotron 300 Tm):

- stretcher ring
- accelerates heavy ions to high energies
- slow extraction

SuperFRS (Fragment Separator):

- analyses and separates secondary beams

CR (Collector Ring complex):


- collects secondary beams
- stochastic precooling of ions and antiprotons
- storage of antiprotons

NESR (New Experimental Storage Ring):


- electron cooling and storage of ions
- in-beam experiments with RIB

HESR (High Energy Storage Ring):

- experiments with antiprotons







Key Parameters: Synchrotrons



Ring	Circumference	Bending Power	Reference Energy	Special Features
SIS 100	1080 m	100 Tm	2.7 GeV/u U^{28+} 29 GeV protons	<ul style="list-style-type: none">• fast pulsed superferric magnets (2 T and 4 T/s)
SIS 300	1080 m	300 Tm	34 GeV/u U^{92+}	<ul style="list-style-type: none">• fast pulsed superconducting $\cos\theta$ magnets (6 T and 1 T/s)

Radioactive Ion Beams (RIB)








For storage ring experiments:

- Fast extraction SIS100

For external target experiments:


- Slow extraction from SIS300
- Slow extraction from SIS100

Compressed Baryonic Matter (CBM)



- U73+ in SIS 100
- U92+ in SIS 300
- Slow Extraction from SIS300


Magnets for the Synchrotrons



SIS 100	Number of Magnets	Aperture (mm)	Magnet Length (m)	Max. Field / Max.Gradient	Max. Ramprate
Dipoles	120	110 x 55	2.6	2 T	4 T/s
Quadru- poles	162	120 x 63 (pole radius: 40)	0.6 1.0 0.6	34.2 T/m 36.7 T/m 34.2 T/m	73.4 T/m/s
SIS 300	Number of Magnets	Aperture (mm)	Magnet Length (m)	Max. Field / Max.Gradient	Max. Ramprate
Dipoles	120	80 (circular)	2.6	6 T	1 T/s
Quadru- poles	132	80 (circular)	0.6 1.0	93 T/m 89 T/m	15.5 T/m/s 14.8 T/m/s

Superconducting Magnets for SIS

100




R&D goals

- **Improvement of DC-field quality**
 - 2D / 3D calculations
- **Guarantee of long term mechanical stability**
($\geq 5 \cdot 10^8$ cycles)
 - concern: coil restraint in the gap, fatigue of the conductor
- **Reduction of eddy / persistent current effects**
(field, losses)

Nuclotron Dipole

- Collaboration: JINR (Dubna)
- Iron Dominated: window frame
- Maximum magnetic field: 2 T
- Ramp rate: 4 T/s
- Hollow-tube superconducting cable
- Two-phase helium cooling





Nuclotron-type Dipole – Loss Mechanisms




Measured Heat Releases to Helium (4K) Triangular cycle: 1Hz, 0-2T	Nuclotron-Dipole (1.4 m)	80KDP2 (1.4 m) (Yoke at 80K)	planned prototype (2.6 m)
Total (W/m)	44	11	
Yoke (W/m)	> 27	0	
Coil (W/m)	12	9	
Static Heat Release (W/m)	5	2	

- **Coil (30%):**
 - main contribution: wire magnetization
⇒ reduction of filament size to 3.5 mm
- **Yoke (70%):**
 - magnetization losses in the central core
 - losses in the endparts due to longitudinal field components B_z

Nuclotron type cable development towards higher currents (BMBF funded)




prototype cable



design principle

photograph of a keystoneed strand



$I_{c \text{ strand}}$: 1400 A @ 2T, 4.46 K →


Proposals





L. Bottura, MN Wilson: ‚perforated tube‘

July 2002 (ASC Houston)

August 2002 (CHATS workshop, Karlsruhe)




P. Bruzzone: ‚C-spring‘ September 2002 (CRPP, Villigen)



V. Keilin: ‚spiral‘ Preliminary report, August 2002

Final report, December 2002






L. Bottura, M. Kauschke, April - June 2002
calculations for ‚C-spring‘ and ‚spiral‘

Alternatives



N-CICC's



C-spring

Pro:

- low friction factor
- low mech. tolerance requirements

Con:

- no circular symmetry
- Strand position undefined near slit
- low Helium exchange

Spiral

Pro:

- good Helium exchange
- circular symmetry

Con:

- high friction factor (x 5 compared to Nuclotron)
- higher mechanical tolerances required

Nuclotron



Pro:

- well defined strand position
- circular symmetry
- low friction factor

Con:

- indirectly cooled strand

AC Losses along Magnet axis z





Z=0: Core edge



- Temperature rise in the end part !

- OPERA-3D calculations of the integral magnetic flux $\Phi_z(z)$


New endblocks



4KDP4



• new 200mm endblock (actual test run)



<= iron yoke
partition and
cooling circuit


• thermometer

Nuclotron-type Dipole – Loss Mechanisms




Measured Heat Releases to Helium (4K) Triangular cycle: 1Hz, 0-2T	Nuclotron-Dipole (1.4 m)	80KDP2 (1.4 m) (Yoke at 80K)	planned prototype (2.6 m) (based on present R&D status)
Total (W/m)	44	11	17
Yoke (W/m)	> 27	0	9
Coil (W/m)	12	9	6
Static Heat Release (W/m)	5	2	2


SIS 100 Dipole - Alternatives



Nuclotron Superferric Window-frame Dipole
(cold bore, cryogenic pumping)



Superferric H-type design
(warm iron, warm bore)




Study at BINP, Russia

Requirements for SIS 100:

Max. Field:	2 T
Max. Ramp Rate:	4 T/s
Field quality:	$\pm 6 \times 10^{-4}$
Aperture:	110x55mm ²

Resistive



Comparison sc and nc 100 Tm dipole



COSTS (M€)	sc	nc
PRODUCTION	36	37
OPERATING	8	45
TOTAL	<u>44</u>	<u>82</u>

based on:



- 248 dipoles (SIS 100 and beamlines)
- 20 years of operation, 6500h/ y
- present status of the R&D
- present aperture (55 x 110)
- operation cycles mix
- present electricity costs

includes costs for

- power supplies, quench detection and protection
- cryogenic system
- tests and operation crew

_saves 17 000 t CO2 /
vear

Vision of the final magnet (4K)



4K-iron

Ceramic aperture spacer

Laminated and horizontally cut
endblocks

Rogowski end profile


Fully symmetric coil

Homogenisation slits



Coil ends restrained

Stainless Steel end plates

Superconducting Accelerator Magnets: SIS 300





- RHIC dipole
- Collaboration with BNL
- Coil dominated: $\cos\theta$
- Maximum field: 3.5 T \Rightarrow 4 T
- Ramp rate: 70 mT/s \Rightarrow 1 T/s !!!
- Supercond. Rutherford cable
- One-phase helium cooling




R&D Goals for RHIC type dipole



- Reduce the effects due to the high ramp rate:
 - lower loss in wire, cable (core) and iron
 - better AC field quality
- Improve the cooling of the Rutherford cable
 - open Kapton insulation with laser cut holes
- Use collars to ensure long-term mechanical stability



collar



Dipole Parameters



RHIC dipole

Superconducting wire:

- NbTi-Cu (1:2.25)
- filament diameter 6 μm
- twist pitch 13 mm
- no coating

Rutherford cable

- no core

Coil

- phenolic spacer
- Cu wedges

Yoke

- $H_c = 145 \text{ A/m}$
- 6.35 mm laminations


RHIC type dipole GSI 001

Superconducting wire:

- NbTi-Cu (1:2.25)
- filament diameter 6 μm
- twist pitch 4 mm
- Stabrite coating

Rutherford cable

- 2 x 25 μm stainless steel core




Coil

- stainless steel collar (G11 keys)
- G11 wedges


Yoke

- $H_c = 33 \text{ A/m}$, 3.5% Silicon
- 0.5 mm laminations, glued

RAMP RATE TESTS



GS1001 QUENCH TESTS



Ramp to 4T
without
quenching:


4T/s – 3
cycles – 2X

2 T/s – 500
cycles – 40
minutes

Thermal time constant ~ 1 min.



by P. Wanderer

Calculated and measured losses for GSI 001



by M.N. Wilson

SIS 300 - Dipole Parameters




UNK Dipole

- 2 layer $\cos\theta$ design
- 80mm bore \Rightarrow 100 mm
- 5.11 T
- 0.11 T/s

Goal: 6T, 1T/s

Study by Technopark Kurchatov
(Kurchatov Institut Moscow,
IHEP, Protvino): **Such a magnet is
feasible, but needs a lot of R&D !**

Summary




- Fast Cycling Superconducting magnets are an important part of the IAF.

We made very good progress , but need more R&D !

Thanks to all members of the collaborations and the magnet group.!

R&D principles








Situation (when we started in 2000)

- small magnet group
- new field
- large variety of magnets
- tight R&D schedule and restricted budget

Consequences



- establish collaborations
- look for existing magnets with similar parameters
- start R&D for dipoles
- build model dipoles with existing material and toolings
⇒ saves time and money

Antiproton Physics



- Antiproton production
 - pauses in SIS100 for cooling in CR
- Antiproton acceleration
 - low repetition rate

Calculated and measured gradients (rate dependent or eddy current terms)




by M.N. Wilson

Calculated and measured intercepts (hysteresis term)



by M.N. Wilson



the theory works pretty well!

good enough to design magnet cooling and refrigeration for the final project

Vision of the final magnet (iron at 80K)

